

JAB MEAS

ថ្នាំទឹកមាសលាយទឹក Aerylie Gold Emudsion

GENERAL INFORMATION JAB MEAS is a Premium Water Base Gold Paint formulated with Green Resin Emulsion for all Fine Art application. JAB MEAS gives a Real Gold effect with a warranty of long durability proven for so many years.

		RÜMINISTURYAY ÉC PE UIUU USE EXTAINT		
ADVANTAGES	 Good Hiding Good-Workability High Gloss Low Odor Anti-Fungal 	 Non- Mercury Crack Bridging Excellent Adhesion Long Lasting Color Scrub Tolerance 		
USE	On	Hard & soft boards, asbestos, ceilings, plaster, concrete and brickwork etc.		
	For	Fine Art Works		
COMPOSITION	Pigments	Super Fine Titanium Dioxide & Mineral Extender		
	Binder	Green Resin Emulsion		
	Thinner	Clean Water		
	Special Additive	Lead free, Ammonia Free, Formaldehyde Free, APEO free		
PROPERTIES	Color	Gold		
	Texture	High-Gloss and Smooth		
	Specific Gravity	1.23+/-0.02 Kgs/Liter		
	Recommended Dry Film Thickness per coat	25-35µ		



JAB MEAS

		Drying Time		Touch Dry: 20-30 minutes Hard Dry : 48 hours		
PROPERTIES	Recoating Interval		2 hours			
		Practical Coverage		133 m²/pail/2coats		
		Packing Content		18 Liters		
		Surface Preparation		Ensure that the surfaces are free from loose particles, dirt, dust, grease, oil, wax. Make good for any surface defected, clean thoroughly and dry.		
INSTRUCTION FOR USE	Application Methods		By using Roller / Soft-Brush Thin with some 10% of clean water and apply by using Roller and/or Soft-Brush			
			By using Air Spray Dilute the paint with 20% of clean water.			
	Previously Painted Surface		Remove all unstable paint film, loose chalk, dust and other foreign matters. Treat surface with Cam-Paint Penetrate Primer "EVERLAST or PROTAN" to strengthen substrate condition.			
		Sequence		cation duct No of Coat		For Old Substrate
RECOMME DED PAIN1 SYSTEM		Plaster	Grade A/B	Grade A/B	2 or 3	
		1 st Primer	Grade A	Grade A	1	EVERLAST/ PROTAN
		2 nd Primer	Gold Primer	Gold Primer	1	Gold Primer
		Finish Coat	JAB MEAS		2 or 3	

NOTE:

The above information is given to the best of our knowledge based on testing and practical application.

However, since we cannot anticipate or control the many conditions under which our products may be used, we can only guarantee the quality of the product itself. We reserve the right to alter the given data without prior notice.