
	CAMBODIAN CHEMICAL SUPPLY CO., LTD.		Doc. No : TDS-PRD-02
	Name	PARROT	Revised No : 0
	Type	Technical Data Sheet	Page No : 1 of 2

<p>PARROT is a High Gloss Architectural Alkyd paint with special additives designed for Iron Black steel and wooden for decorative Very good quality and use for exterior and Interior for long Lasting.</p>		
ADVANTAGES	<ul style="list-style-type: none"> • High Gloss and easy to use • Very Good Color Retention & Gloss Retention • Very good adhesion and Surface Hardness • For Long Lasting 	
USE	<i>On</i>	Black and Galvanized steel Surface, and Soft and hard Wood,
	<i>For</i>	Decoration and protection of the above Surface and long Durability.
COMPOSITION	<i>Pigments</i>	- Fine particle Titanium dioxide, - Non-Lead Chromate Colorant
	<i>Binder</i>	Type : Alkyd Resin Reference : Haiphong
	<i>Thinner</i>	Cam-Paint thinner DW-5050
	<i>Special Additive</i>	Drier : Lead (Pp.) free Preservative : Mercury free Reference : TROY
PRODUCT PROPERTIES	<i>Solid %</i>	By Volume: 57
	<i>Color</i>	- Multi Choices - Reference: CLARIANT ,POPCO, PANEX Pigment
	<i>Texture</i>	High Gloss (GU:91 @60°)
	<i>Specific Gravity</i>	1 ±03 g/ml
	<i>Drying Time @ room temperature</i>	Touch dry: 3-4H
	<i>Recommended Wet Film Thickness Per Coat</i>	45 –60µm
	<i>Recommended Dry Film Thickness Per Coat</i>	30-45µm

 CAM-PAINT គ្រីណិស៊ី	CAMBODIAN CHEMICAL SUPPLY CO., LTD.		Doc. No : TDS-PRD-02
	Name	PARROT	Revised No : 0
	Type	Technical Data Sheet	Page No : 2 of 2

	<i>Recoating Interval</i>	8-12hours @ 30oC
	<i>Practical Coverage</i>	7m ² /kg/coat Smooth Surface
	<i>Pack Size</i>	1 kg/metal pail; (3.8 kgx4)(1kgx12)/cotton box
INSTRUCTION FOR USES	<i>Surface Preparation</i>	Ensure that the surfaces are free from loose particles, dirt, dust, grease, oil, wax. Make good for any surface defected, clean thoroughly and dry.
	<i>Application Methods</i>	<p>By using Roller / Soft-Brush Thin with 10% of DW-5050 thinner and apply by using Roller and/or Soft-Brush.</p> <p>By Using Air Spray Dilute the paint with 20% of DW-5050 thinner</p>
	<i>Previously Painted Surface</i>	Remove all unstable paint film, loose chalk, dust and other foreign matters.

Sequence	Complement Product			No of Coat	Remark
	<i>Black steel</i>	<i>Wood</i>	<i>Concrete</i>		
Primer	Red& Gray primer	Special primer	N/A	1	1 coat of Primer & 1-2 coat of Top Coat

NOTE:

The above information is given to the best of our knowledge based on testing and practical application.

However, since we cannot anticipate or control the many conditions under which our products may be used, we can only guarantee the quality of the product itself. We reserve the right to alter the given data without prior notice.

Contact for further information:
 Mr. Vey Bora, Production Manager
 H/P: (+855) 15 888 003 / 78 885 443
 E-mail: veybora@campaint-ccsc.com.kh