

VITAL Ultra-Fine

GENERAL INFORMATION

VITAL Ultra-Fine is GREEN EMULSION "Semi-Gloss" PREMIUM AQUEOUS PAINT. It is specially formulated for *all weathers*. This premium paint is excellent adhesion on exterior (façade) and interior walls.

VITAL Ultra-Fine is Water Resistant, Water Repellent, Excellent Scrub Resistant resists fungus, flaking, chalking and it has been proven to be extremely durable through weathers.

| proven to be extremely durable through weathers. | | | | | |
|--|--|---|--|--|--|
| ADVANTAGES | Good HidingWell-WorkabilitySemi-GlossLow OdorAnti-Fungal | Non- Mercury Crack Bridging Excellent Adhesion Long Lasting Color Scrub Tolerance | | | |
| USE | On | Hard & soft boards, asbestos, ceilings, plaster, concrete and brickwork etc. | | | |
| | For | Decoration and protection of the above stated substrate. | | | |
| COMPOSITION | Pigments | 80% Titanium Dioxide and 20% Specialty Kaolin | | | |
| | Binder | Green Pure Acrylic Emulsion - 45% of total volume | | | |
| | Thinner | Clean Water | | | |
| | Special Additive | Lead free, Ammonia Free, Formaldehyde Free, APEO free | | | |
| PROPERTIES | Color | Multi Choices | | | |
| | Texture | Semi-Gloss and Smooth | | | |
| | Specific Gravity | 1.23+/-0.02 Kg/ Liter | | | |
| | Recommended Dry Film Thickness per coat | 30-40μ | | | |
| | Drying Time | Touch Dry: 20-30 minutes Hard Dry: 48 hours | | | |



VITAL

Ultra-Fine

| PROPERTIES | Recoating Interval | | 2 hours | | |
|--------------------------|-------------------------------|----------------------------|---|------------|----------------------|
| | Practical Coverage | | 111 m²/pail/2coats | | |
| | Packing Content | | 15 Liters | | |
| INSTRUCTION FOR USE | Surface Preparation | | Ensure that the surfaces are free from loose particles, dirt, dust, grease, oil, wax. Make good for any surface defected, clean thoroughly and dry. | | |
| | Application Methods | | By using Roller / Soft-Brush Thin with some 10% of clean water and apply by using Roller and/or Soft-Brush. By using Air Spray Dilute the paint with 20% of clean water. | | |
| | Previously Painted Surface | | Remove all unstable paint film, loose chalk, dust and other foreign matters. Treat surface with Cam-Paint Penetrate Primer "EVERLAST PROTAN" to strengthen substrate condition. | | |
| RECOMMENI PAINT SYSTE | Sequence | Application Product | | No of Coat | For Old |
| | | Exterior | Interior | 0 02 0000 | Substrate |
| | Plaster | Grade A | Grade A | 2 or 3 | |
| | Primer | Grade A | Grade A | 1 | EVERLAST / PROTAN |
| | Finish Coat | VITAL | | 2 or 3 | |

NOTE:

The above information is given to the best of our knowledge based on testing and practical application.

However, since we cannot anticipate or control the many conditions under which our products may be used, we can only guarantee the quality of the product itself. We reserve the right to alter the given data without prior notice.